

EUROFIBRE

EMULSION BOUND CSM

Eurofibre is an emulsion bound chopped strand mat, which is manufactured to a very high standard, for use in hand lay up applications.

It is produced from a high integrity strand which has a good speed of wet-out.

Eurofibre CSM is soft to handle, and the binder ensures excellent drapeability and moulding performance.

These characteristics combine to ensure that the mat has good air release and an excellent overall performance.

Eurofibre CSM is suitable for use with all types of unsaturated polyester resins and resin to glass ratios in the range of 1.5:1 to 2.5:1 can be achieved with ease.

USER BENEFITS:

- Excellent drapeability.
- Suitable for single and multiply moulding.
- Good air release.
- Low Resin Consumption.



Unlimited. **DSM**

www.euroresins.com

**euro
resins**

EUROFIBRE

EMULSION BOUND CSM

PRODUCT DESCRIPTION.

<u>Property</u>	<u>Description</u>
Glass Type	E
Filament Diameter μm	11
Binder Type	Emulsion
Coupling Agent	Silane
Mat Density g/m^2	300, 450, 600 & 900
Mat Width meters	0.95, 1.27 & 1.37

PACKAGING.

Each roll in polythene bag and cardboard box.
12 and or 16 rolls per pallet depending on mat width.
Roll diameter 30cm.
Roll weight (nominal 0.95m) 30kg.
Pallets stretched wrapped.

STORAGE.

Chopped strand mat should be stored in the original packaging and protected from impact damage. It is recommended that glass fiber be kept at a temperature not exceeding 25°C and a relative humidity of 65% \pm 10%. Boxes of chopped strand mat should preferably be stored on end. If boxes are stored on their sides, no more than three boxes should be stacked on top of each other if damage to the mat is to be avoided. A First-In-First-Out (FIFO) stock control system is recommended to minimize the influence of storage conditions.



Euro Resins Europe Holding GmbH & Co. KG
Telephone: +49 7031 2861 0
Fax: +49 7031 281 306

Unlimited. **DSM**

www.euroresins.com

