

## BÜFA®-Release Wax Liquid

Liquid Mould Release Wax

Prod. No. 741-0063

**Product description** BÜFA®-Release Wax Liquid is a release agent on a polyethylene wax base dissolved in white spirit.

**Applications** BÜFA®-Release Wax Liquid is used as a mould release agent when producing UP and EP resin mouldings in complicated moulds made of plastic, wood, gypsum, etc. When using BÜFA®-Release Lacquer, BÜFA®-Release Wax Liquid is used as an additional aid to ensure reliable demoulding and is applied first, before the layer of Release Lacquer is applied.

Specifications / technical data	Property	Test method	Value	Unit
	Density at 20 °C	DIN 53 217/2	approx. 0,79	g/ml
	Flash point	DIN 53 213	39	°C

**Directions for use** BÜFA®-Release Wax Liquid can be applied with a wool or cotton cloth as well as with a brush. Synthetic fabrics or bristles are not suitable because the release agent contains white spirit which dissolves synthetic materials and would leave smears on the surface. The liquid wax should be applied evenly in a thin layer. Before the wax film dries it should be rubbed with a soft cloth to make sure it is evenly distributed.

Before a new mould is put into operation, the wax should be applied very thoroughly, i.e. it should be waxed 2 or 3 times consecutively. This ensures that all pores on the surface of the mould are closed. The wax on moulds that have been put into operation only needs to be reapplied after every fifth to sixth demoulding.

**Note:** Shake the container of BÜFA®-Release Wax Liquid well before using!

**Storage/Handling** This product must be stored cool in closed containers, protected from sunlight. Shelf-life is at least 12 months in unopened, original containers stored up to a temperature of 20 °C.

# BÜFA®-Release Wax Liquid

**Liquid Mould Release Wax**

Prod. No. 741-0063

Note: The Information given above is based on our current state of knowledge and experience. In view of the many factors that may influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. No legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of our products to observe proprietary rights as well as existing laws and regulations. The latest version of the corresponding EU Safety Data Sheet must also be observed.

BÜFA Composite Systems GmbH & Co. KG  
Hohe Looge 2-8  
26180 Rastede  
GERMANY  
Phone +49 4402 975-0  
Fax +49 4402 975-300  
compositesystems@buefa.de  
www.buefa.de  
www.buefacompositesystems.com

A member of the BÜFA-Group