

PRO-VAC S1141 & S1140 vacuum bagging sealant tape Low to medium temperature sealant tape

Description:

- Recommended for use in vacuum infusion, wet lay-up bagging and bag to bag (envelope bagging) processing.
- · Compatible with most vacuum films and tool surfaces but pre-production trials are advisable.
- We recommend that the tape is removed at room temperature.

Technical data:

Max use temperature	130°C - bag to tool and bag to bag	
colour	Black	0
Standard roll sizes PVS1141 PVS1140	3,3mm x 12mm x 15m 2,5mm x 12mm x 15m	
Standard packaging PVS1141 PVS1140	22 rolls per box - 36 boxes per pallet 28 rolls per box - 48 boxes per pallet	

Packaging and storage

Store in original and unopened packaging and protected from humidity Store at a maximum temperature of 30°C in a ventilated environment Material has a 12 month shelf life from date of manufacture Store flat with a maximum of 4 boxes stacked



HF Industri & Marine ApS Gotlandsvej 6 5700 Svendborg Denmark Phone: +45 62 20 13 12 • Fax: +45 62 20 14 77 • info@hfmarine.dk • www.hfmarine.dk

All statements, technical information and recommendations, including storage, contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability of this particular purpose and shall assume all risk and liability in connection herewith.