Technical Data Sheet



OLDOPAL-Mould Cleaner 3125

Liquid Mould Cleaner

Prod. No. 742-0596

Product description

OLDOPAL-Mould Cleaner 3125 is a highly effective cleaning agent on a solvent base that is used to remove the remains of wax and polyester that may build up on the surface of moulds with increasing numbers of demouldings.

Applications

OLDOPAL-Mould Cleaner 3125 is a liquid mould cleaner that is used to clean production moulds made of all conventional mould making materials (glass fibre reinforced polyester, glass fibre reinforced epoxy resin, steel, aluminium, glass, etc.)

Specifications / technical data

Property	Test method	Value	Unit
Density at 20 °C	DIN 53 217/2	ca. 0.8	g/ml
Flow viscosity at 20 °C in an ISO-cup 4 mm Ø	EN ISO 2431	11 - 13	S
Flash point	DIN 53 213	+ 23	°C

Directions for use

Apply OLDOPAL-Mould Cleaner 3125 to the areas to be cleaned with a soft rag and allow the cleaner to act. Do not distribute over large areas because the product evaporates very quickly. After approx. 30 - 60 seconds, work over the area with moderate pressure until the soiling has been removed. Since the surface may be attacked if allowed to act too long, never leave damp rags on plastic surfaces for longer periods of time! If there is any question about the resistance of the mould's surface, test first on an area that will not be visible later.

After the applied mould cleaner has evaporated, the surface must be wiped off dry. Release agent should then be reapplied to the mould. The pleasant odour of the mould cleaner should not lead to careless handling; observe the Safety Data Sheet!

Storage/Handling

This product must be stored cool in closed containers, protected from sunlight. Shelf-life is at least 12 months in unopened, original containers stored up to a temperature of 25 °C.

Note: The Information given above is based on our current state of knowledge and experience. In view of the many factors that may Influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. No legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of our products to observe proprietary rights as well as existing laws and regulations. The latest version of the corresponding EU Safety Data Sheet must also be

Rev. dated: 2013-06-13 Version: 1 Page



OLDOPAL-Mould Cleaner 3125

Liquid Mould Cleaner

Prod. No. 742-0596

observed.

BÜFA Composite Systems GmbH & Co. KG Hohe Looge 2-8 26180 Rastede GERMANY Phone +49 4402 975-0 Fax +49 4402 975-300 compositesystems@buefa.de www.buefa.de www.buefacompositesystems.com

A member of the BÜFA-Group

Rev. dated: 2013-06-13 Version: 1 Page